Hovsepian v. Apple, Inc.

Doc. 70 Att. 11

EXHIBIT 12

Dockets.Justia.com

US006002720A

United States Patent [19]

Yurt et al.

[11] **Patent Number: 6,002,720**

[45] **Date of Patent: Dec. 14, 1999**

[54] **AUDIO AND VIDEO TRANSMISSION AND RECEIVING SYSTEM**

[75] Inventors: **Paul Yurt**, Scottsdale, Ariz.; **H. Lee Browne**, Greenwich, Conn.

[73] Assignee: **H. Lee Browne, D/B/A Greenwich Information Technologies LLC**, Greenwich, Conn.

[21] Appl. No.: **08/630,590**

[22] Filed: **Apr. 10, 1996**

Related U.S. Application Data

[63] Continuation of application No. 08/133,982, Oct. 8, 1993, Pat. No. 5,550,863, which is a continuation of application No. 07/862,508, Apr. 2, 1992, Pat. No. 5,253,275, which is a continuation of application No. 07/637,562, Jan. 7, 1991, Pat. No. 5,132,992.

[51] **Int. Cl.**[6] **H04N 7/10**

[52] **U.S. Cl.** **375/240**; 375/259; 375/377; 455/4.2; 348/7; 348/8

[58] **Field of Search** 375/240, 259, 375/295, 316, 377; 348/1, 6–8, 10, 12–14, 17, 384, 385, 387, 470, 473, 906; 379/90.1, 93.08, 93.1, 101.1, 102.1–102.3; 455/2, 3.1, 4.1, 4.2, 5.1, 6.3

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,599,178	8/1971	Jackson et al.	340/172.5
3,673,318	6/1972	Olsen et al. .	
3,746,780	7/1973	Stetten et al.	178/6.6 A
3,919,462	11/1975	Hartung et al. .	
4,009,344	2/1977	Flemming	179/15 BS
4,009,346	2/1977	Parker et al.	179/15 AQ
4,028,733	6/1977	Ulicki	358/86
4,062,043	12/1977	Zeidler et al.	358/86
4,071,697	1/1978	Bushnell et al.	179/2 TV
4,122,299	10/1978	Cannon	178/26 A
4,206,316	6/1980	Burnsweig et al.	375/43
4,245,245	1/1981	Matsumoto et al. .	
4,280,139	7/1981	Mogi et al. .	
4,295,154	10/1981	Hata et al.	358/4
4,333,110	6/1982	Faerber et al. .	
4,354,201	10/1982	Sechet et al. .	
4,381,522	4/1983	Lambert	358/86
4,400,717	8/1983	Southworth et al.	358/13
4,450,477	5/1984	Lovett	358/86
4,488,179	12/1984	Krüger et al. .	
4,506,387	3/1985	Walter	455/612
4,518,989	5/1985	Yabiki et al.	358/86
4,521,806	6/1985	Abraham	358/86
4,533,936	8/1985	Tiemann et al.	358/12
4,538,176	8/1985	Nakajima et al.	358/86
4,567,512	1/1986	Abraham	358/86
4,590,516	5/1986	Abraham	358/86

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

0 309 298	9/1989	European Pat. Off. .
0355697A2	2/1990	European Pat. Off. .
83/02208	6/1983	WIPO .
WO84/00863	3/1984	WIPO .
WO89/12370	12/1989	WIPO .

OTHER PUBLICATIONS

Sandburg, "E–Data Backs Off Patent Claims," *The Recorder* (Apr. 2, 1999).

Ernie Ohrenstein, "Supercomputers Seek High Throughput and Expandable Storage", Computer Technology Review, IEEE Spectrum, May, 1990, pp. 33–43.

Patricia A. Morreale, et al., "Metropolitan–Area Networks," IEEE Spectrum, May 1990, pp. 40–43.

Primary Examiner—Amanda T. Le

Attorney, Agent, or Firm—Andrea G. Reister; Erik B. Milch; Howrey & Simon

[57] **ABSTRACT**

A system of distributing video and/or audio information employs digital signal processing to achieve high rates of data compression. The compressed and encoded audio and/or video information is sent over standard telephone, cable or satellite broadcast channels to a receiver specified by a subscriber of the service, preferably in less than real time, for later playback and optional recording on standard audio and/or video tape.

11 Claims, 12 Drawing Sheets


RETRIEVE INFORMATION FOR SELECTED ITEMS
ASSIGN UNIQUE IDENTIFICATION CODE
PLACE DATA IN PRE-DETERMINED FORMAT
SEQUENCE DATA
COMPRESSING THE DATA
STORE AS A FILE
STORE IN LARGE CAPACITY STORAGE
RECEIVE TRANSMISSION REQUEST
SEND TO REMOTE LOCATION
RECEIVE AT REMOTE LOCATION
BUFFER THE DATA
PLAYBACK AT TIME REQUESTED

U.S. PATENT DOCUMENTS

4,636,876	1/1987	Schwartz .	
4,679,079	7/1987	Catros et al.	358/135
4,688,246	8/1987	Eilers et al.	380/9
4,734,764	3/1988	Pocock et al. .	
4,734,765	3/1988	Okada et al.	358/102
4,755,872	7/1988	Bestler et al.	358/86
4,755,889	7/1988	Schwartz .	
4,763,191	8/1988	Gordon et al.	358/86
4,785,349	11/1988	Keith et al.	358/136
4,792,849	12/1988	McCalley et al. .	
4,807,023	2/1989	Bestler et al.	358/86
4,829,372	5/1989	McCalley et al. .	
4,833,710	5/1989	Hirashima	380/20
4,847,677	7/1989	Music et al.	358/13
4,847,827	7/1989	Tompkins et al.	370/62
4,868,653	9/1989	Golin et al.	358/133
4,890,320	12/1989	Monslow et al.	380/10
4,907,081	3/1990	Okamura et al.	358/133
4,914,508	4/1990	Music et al.	358/13
4,920,432	4/1990	Eggers et al.	360/33.1
4,937,821	6/1990	Boulton	370/124
4,947,244	8/1990	Fenwick et al.	358/86
4,949,169	8/1990	Lumelsky et al.	358/86
4,949,187	8/1990	Cohen	358/335
4,963,995	10/1990	Lang	358/335
4,975,771	12/1990	Kassatly .	
5,014,267	5/1991	Tompkins et al.	370/62
5,032,927	7/1991	Watanabe et al.	398/133 X
5,057,927	10/1991	Lang .	
5,057,932	10/1991	Lang	358/133
5,062,136	10/1991	Gattis et al. .	
5,091,938	2/1992	Thompson et al. .	
5,093,718	3/1992	Hoarty et al.	358/84
5,109,414	4/1992	Harvey et al. .	
5,113,496	5/1992	McCalley et al. .	
5,119,188	6/1992	McCalley et al. .	
5,129,036	7/1992	Dean et al. .	
5,130,792	7/1992	Tindell et al.	348/7
5,132,992	7/1992	Yurt	375/122
5,133,079	7/1992	Ballantyne et al.	348/7
5,164,839	11/1992	Lang	358/335
5,191,573	3/1993	Hair .	
5,195,092	3/1993	Wilson et al.	348/13
5,239,540	8/1993	Rovira et al. .	
5,249,164	9/1993	Koz .	
5,276,866	1/1994	Paolini	395/603
5,341,175	8/1994	Koz .	
5,381,347	1/1995	Gery .	
5,473,362	12/1995	Fitzgerald et al. .	
5,502,503	3/1996	Koz .	
5,517,257	5/1996	Dunn et al. .	
5,566,301	10/1996	Koz et al. .	
5,581,297	12/1996	Koz et al. .	
5,592,233	1/1997	Koz .	
5,594,730	1/1997	Koz et al. .	
5,600,368	2/1997	Matthews, III .	
5,630,094	5/1997	Hayek et al. .	
5,644,355	7/1997	Koz et al. .	
5,648,824	7/1997	Dunn et al. .	
5,654,748	8/1997	Matthews, III .	
5,675,734	10/1997	Hair .	
5,687,331	11/1997	Volk et al. .	
5,701,511	12/1997	Smith .	
5,721,829	2/1998	Dunn et al. .	
5,721,950	2/1998	Tobagi et al. .	
5,724,543	3/1998	Ozden et al. .	
5,732,239	3/1998	Tobagi et al. .	
5,734,119	3/1998	France et al. .	
5,734,925	3/1998	Tobagi et al. .	
5,737,495	4/1998	Adams et al. .	
5,742,773	4/1998	Blomfield-Brown et al. .	
5,751,282	5/1998	Girard et al. .	
5,774,172	6/1998	Kapell et al. .	
5,781,228	7/1998	Sposato .	
5,793,980	8/1998	Glaser et al. .	
5,799,113	8/1998	Lee .	
5,801,692	9/1998	Muzio et al. .	
5,802,394	9/1998	Baird et al. .	
5,815,145	9/1998	Matthews, III .	
5,815,195	9/1998	Tam .	
5,815,662	9/1998	Ong .	
5,815,689	9/1998	Shaw et al. .	
5,818,972	10/1998	Girod et al. .	
5,826,110	10/1998	Ozden et al. .	
5,832,309	11/1998	Noe et al. .	
5,835,495	11/1998	Ferriere .	
5,844,594	12/1998	Ferguson .	
5,852,705	12/1998	Hanko et al. .	
5,861,906	1/1999	Dunn et al. .	

FIG. 1a


100
200
TRANS-
MISSION
SYSTEM
ISDN
RE-
CEPTION
SYSTEM

FIG. 1b


100
TRANS-
MISSION
SYSTEM
RE-
CEPTION
SYSTEM
200'''
RE-
CEPTION
SYSTEM
200"
RE-
CEPTION
SYSTEM
200
RE-
CEPTION
SYSTEM
200'
RE-
CEPTION
SYSTEM

FIG. 1d


100
TRANSMISSION
SYSTEM
COMMON
CHANNEL
200
RECEPTION
SYSTEM
USER
USER
USER
USER

FIG. 1c


REMOTE ORDER PROCESSING AND ITEM DATABASE
300
TRANS-MISSION SYSTEM
100
100'
100"
100'''
RECEP-TION SYSTEM
200
200'
200"
200'''

FIG. 1e


100
TRANSMISSION SYSTEM
200
RECEPTION SYSTEM
200'
RECEPTION SYSTEM
USER
USER
USER
USER
USER
USER
200a
200b

FIG. 1f


100
TRANSMISSION SYSTEM
200
RECEPTION SYSTEM
USER
200'
RECEPTION SYSTEM
200c
USER
USER
USER
USER
USER
USER
200a
200b

FIG. 1g


100
TRANSMISSION SYSTEM
200
RECEPTION SYSTEM
200d
USER
USER
USER
USER
USER
USER

FIG. 4


USER LOGS ON
4010
4000
FIND DESIRED PROGRAM
4020
SELECT PROGRAM FOR TRANSMISSION
4030


100
SOURCE MATERIAL LIBRARY
111
IDENTI-FICATION ENCODING PROCESS
112
113
ANALOG
127
AUDIO
VIDEO
123
A/D CON-VERSION
123a
123b
DIGITAL
124
AUDIO
VIDEO
FORMAT CON-VERSION
125a
125b
125
TIME ENCODING
114
PRE COM-PRESSION DATA PROCESSING
115
115a
130
AUDIO
131
VIDEO
115b
128
AUDIO
VIDEO
129
116
COMPRESSED DATA FORMATTING SECTION
117
117'
TO THE COMPRESSED DATA LIBRARY(S)

FIG. 2a



118
COMPRESSED DATA LIBRARY
HIGH SPEED NETWORK
119
TRANSMISSION FORMAT CONVERSION CPU
122
TRANS-CEIVER
TO CUSTOMER'S RECEIVING SYSTEM
ISDN
ISDN
ISDN
TRANSMISSION FORMAT CONVERSION CPU
TRANS-CEIVER
B ISDN
B ISDN
B ISDN
TRANSMISSION FORMAT CONVERSION CPU
TRANS-MITTER
SATELLITE
CABLE TV
TRANSMISSION FORMAT CONVERSION CPU
TRANS-CEIVER
LAN OR MAN
100
1123
LIBRARY SYSTEM CONTROL COMPUTER
TRANSMISSION FORMAT CONVERSION CPU
TRANS-CEIVER
TELEPHONE
TELEPHONE
TELEPHONE
TELEPHONE
121
LIBRARY ACCESS INTER-FACE
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS
OPERATOR OR CUSTOMER ACCESS

FIG. 2b


CALL SYSTEM ACCESS NUMBER
3010
RECEIVE INSTRUCTIONS
3020
ENTER I.D. CODE
3030
CONFIRMATION OF STANDING
3040
QUEUE USER FOR SELECTION CODE
3050
3000
USER ENTERS SELECTION CODE
3060
CONFIRM SELECTION SET PRICE
3070
NO
CONFIRMATION CORRECT
3080
YES
USER MAY ENTER TIME AND DESTINATION
3090
USER CONFIRMS ORDER IS CORRECT
3100
ORDER PLACED ON TRANSMISSION QUEUE
3110

FIG. 3


CONFIRM AVAILABILITY
5010
PHYSICAL CON-NECTION TO RECEIVER
5020
CONFIRM CONNECTION
5030
TRANSFER FROM LARGE CAPACITY STORAGE
5040
SEND TO RECEIVER
5050
CONFIRMATION OF RECEIVED DATA
5060
BREAK PHYSICAL CONNECTION
5070
CONFIRMATION
5080
UPDATE ACCOUNT
5090

FIG. 5


400
RETRIEVE INFORMATION FOR SELECTED ITEMS
412
ASSIGN UNIQUE IDENTIFICATION CODE
413a
PLACE DATA IN PRE-DETERMINED FORMAT
413b
SEQUENCE DATA
413c
COMPRESSING THE DATA
413d
STORE AS A FILE
413e
STORE IN LARGE CAPACITY STORAGE
414
RECEIVE TRANS-MISSION REQUEST
415
SEND TO REMOTE LOCATION
416
RECEIVE AT REMOTE LOCATION
417
BUFFER THE DATA
418
PLAYBACK AT TIME REQUESTED
419

FIG. 7


COMPRESSED
DIGITAL VIDEO
AUDIO
ANALOGUE VIDEO
AUDIO
REAL TIME
OUTPUT FORMAT CONVERSION
206
203
211
212
213
214
205
DECOM-PRESSION
VIDEO
AUDIO
208
209
RECEIVER FORMAT CONVERSION
202
DATA FORMATTING
204
200
TRANSCEIVER
201
USER/ COMPUTER INTERFACE
207
OTHER TRANSMISSION TIME FROM AUDIO AND VIDEO TRANSMISSION SYSTEM VIA: ISDN, BROADBAND ISDN, SATELLITE, COM-PUTER ETC...
TO AUDIO & VIDEO TRANS-MISSION SYSTEM
VIEWER CONTROL INTERFACE

FIG. 6


811
ONE VIDEO SAMPLE
ONE VIDEO FRAME
811
812
812
FRAME 1
ONE SECOND OF VIDEO
FRAME 3
FRAME4
FRAME 5
813
FRAME 30

FIG. 8a


831
ONE DATA BYTE
BYTE 1
ONE DATA FRAME
BYTE 3
BYTE 4
BYTE 5
831
832
BYTE N

FIG. 8c



821
ONE AUDIO SAMPLE
SAMPLE 1
ONE AUDIO FRAME
SAMPLE 3
821
SAMPLE 4
SAMPLE 5
822
SAMPLE 1470
FRAME 1
ONE SECOND OF AUDIO
FRAME 3
822
FRAME4
FRAME 5
823
FRAME 30

FIG. 8b

FIG. 8d



ITEM 1
ITEM 2
ITEM 3
812
832
822
D V D A V D A V D A V D A V D A V D
D V V A V V A V V A V V A V V A
D A A A A A A D A A A A A A A


DISTRIBUTION CHANNEL 1
BLOCK 1
BLOCK 2
BLOCK 3
BLOCK 1
BLOCK 2
BLOCK 2
DISTRIBUTION CHANNEL 2
BLOCK 4
DISTRIBUTION CHANNEL 3
BLOCK 1
DISTRIBUTION CHANNEL 4
BLOCK 5
TIME

FIG. 8e

AUDIO AND VIDEO TRANSMISSION AND RECEIVING SYSTEM

This is a continuation of application Ser. No. 08/133,982, filed Oct. 8, 1993, U.S. Pat. No. 5,550,863 which is a continuation application of prior application Ser. No. 07/862,508 filed Apr. 2, 1992 which issued as U.S. Pat. No. 5,253,275 on Oct. 12, 1993, which is a continuation application of prior application Ser. No. 07/637,562 filed Jan. 7, 1991 which issued as U.S. Pat. No. 5,132,992 on Jul. 21, 1992.

BACKGROUND OF THE INVENTION

The present invention relates generally to an audio and video transmission and receiving system, and more specifically to such a system in which the user controls the access and the playback operations of selected material.

At the present time, only a video cassette recorder (VCR) or a laser disk player (LDP) allow a viewer to enjoy control over selection of particular audio/video material. Using either a VCR or an LDP requires the viewer to obtain a video tape either by rental or by purchase. Remote accessing of the material has not yet been integrated into an efficient system.

Several designs have been developed which provide the viewer with more convenient means of accessing material. One such design is disclosed in U.S. Pat. No. 4,506,387, issued to Walter. The Walter patent discloses a fully dedicated, multi-conductor, optical cable system that is wired to the viewer's premises. While the system affords the viewer some control over accessing the material, it requires that a location designated by the viewer be wired with a dedicated cable. The Walter system further requires the viewer be at that location for both ordering and viewing the audio/video material.

U.S. Pat. No. 4,890,320, issued to Monslow, describes a system which broadcasts viewer selected material to a viewer at a prescribed time. This system is limited in that it requires multiple viewers in multiple locations to view the audio/video material at the time it is broadcast, rather than allowing each viewer to choose his or her own viewing time. The system disclosed in Monslow also does not allow for the stop, pause, and multiple viewing functions of existing VCR technology.

U.S. Pat. No. 4,590,516, issued to Abraham, discloses a system that uses a dedicated signal path, rather than multiple common carriers, to transmit audio/video programming. The receiver has no storage capability. The system provides for only display functions, which limits viewing to the time at which the material is ordered. Like Monslow, the Abraham system does not allow for the stop, pause, and multiple viewing functions of existing VCR technology.

U.S. Pat. No. 4,963,995, issued to Lang, discloses an audio/video transceiver with the capability of editing and/or copying from one video tape to another using only a single tape deck. Lang does not disclose a system with one or more libraries wherein a plurality of system subscribers may access information stored in the film and tape library or libraries, and play back the selected information at a time and place selected by the subscriber.

It is therefore an object of the present invention to provide a user with the capability of accessing audio/video material by integrating both accessing and playback controls into a system that can use multiple existing communications channels.

It is a further object of the present invention to provide a picture and sound transmission system which allows the user to remotely select audio/video material from any location that has either telephone service or a computer.

A still further object of the present invention is to provide a picture and sound transmission system wherein the selected audio/video material is sent over any one of several existing communication channels in a fraction of real time to any location chosen by the user that has a specified receiver.

Another object of the present invention is to provide a picture and sound transmission system wherein the user may play back the selected audio/video material at any time selected by user and retain a copy of the audio/video material for multiple playbacks in the future.

Another object of the present invention is to provide a picture and sound transmission system wherein the information requested by the user may be sent as only audio information, only video information, or as a combination of audio and video information.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

SUMMARY OF THE INVENTION

To achieve the objects in accordance with the purposes of the present invention, as embodied and described herein, the transmission and receiving system for providing information to remote locations comprises source material library means prior to identification and compression; identification encoding means for retrieving the information for the items from the source material library means and for assigning a unique identification code to the retrieved information; conversion means, coupled to identification encoding means, for placing the retrieved information into a predetermined format as formatted data; ordering means, coupled to the conversion means, for placing the formatted data into a sequence of addressable data blocks; compression means, coupled to the ordering means, for compressing the formatted and sequenced data; compressed data storing means, coupled to the compression means, for storing as a file the compressed sequenced data received from the compression means with the unique identification code assigned by the identification encoding means; and transmitter means, coupled to the compressed data storing means, for sending at least a portion of a specific file to a specific one of the remote locations.

The present invention further comprises a distribution method responsive to requests identifying information to be sent from a transmission system to a remote location, the method comprising the steps of storing audio and video information in a compressed data form; requesting transmission, by a user, of at least a part of the stored compressed information to the remote location; sending at least a portion of the stored compressed information the remote location; receiving the sent information at the remote location; buffering the processed information at the remote location; and playing back the buffered information in real time at a time requested by the user.

Additionally, the present invention comprises a receiving system responsive to a user input identifying a choice of an item stored in a source material library to be played back to the subscriber at a location remote from the source material library, the item containing information to be sent from a transmitter to the receiving system, and wherein the receiving system comprises transceiver means for automatically receiving the requested information from the transmitter as compressed formatted data blocks; receiver format conversion means, coupled to the transceiver means, for converting the compressed formatted data blocks into a format suitable for storage and processing resulting in playback in real time; storage means, coupled to the receiver format conversion means, for holding the compressed formatted data; decompressing means, coupled to the receiver format conversion means, for decompressing the compressed formatted information; and output data conversion means, coupled to the decompressing means, for playing back the decompressed information in real time at a time specified by the user.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate the presently preferred apparatus and method of the invention and, together with the general description given above and the detailed description of the preferred embodiment given below serve to explain the principles of the invention. In the drawings:

FIGS. 1*a*–1*g* are high level block diagrams showing different configurations of the transmission and receiving system of the present invention;

FIGS. 2*a* and 2*b* are detailed block diagrams of preferred implementations of the transmission system of the present invention;

FIG. 3 is a flowchart of a preferred method of ordering a selection from a library in accordance with the present invention;

FIG. 4 is a flowchart of a preferred method of user request via a user interface of the present invention;

FIG. 5 is a flowchart of a preferred method of implementing a queue manager program of the present invention;

FIG. 6 is a block diagram of a preferred implementation of the receiving system of the present invention;

FIG. 7 is a flowchart of a preferred method of distribution of the present invention; and

FIGS. 8*a*–8*e* are block diagrams of preferred implementation of data structures and data blocking for items in the audio and video distribution system of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

FIGS. 1*a*–1*g* are high level block diagrams showing different configurations of the transmission and receiving system of the present invention. FIGS. 1*a*, 1*b*, 1*d*, 1*e*, 1*f*, and 1*g* each show transmission system **100**, described in more detail below with respect to FIGS. 2*a* and 2*b*. A user of the transmission and receiving system of the present invention preferably accesses transmission system **100** by calling a phone number or by typing commands into a computer. The user then chooses audio and/or video material from a list of available items which he or she wants to listen to and/or watch.

As shown in FIG. 1*a*, the transmission and receiving system may preferably comprise a peer to peer configuration where one transmission system **100** communicates with one reception system **200**. As shown in FIG. 1*b*, the transmission and receiving system of the present invention may alternatively comprise a plurality of reception systems **200**, **200'**, **200''**, and **200'''**, which are each associated with a single transmission system **100**.

FIG. 1*c* shows a high level block diagram of the transmission and receiving system of the present invention including remote order processing and item database **300**, described in more detail with respect to FIG. **3**. Remote order processing and item database **300** preferably enables users to access desired items by remote communication. The remote order processing and item database **300** may communicate with a plurality of transmission systems **100**, **100'**, **100''**, and **100'''**, each of which communicates with a respective set of reception systems **200**, **200'**, **200''**, and **200'''**. Each of the reception systems in sets **200**, **200'**, **200''**, and **200'''** may preferably communicate with a plurality of users.

FIG. 1*d* shows a high level block diagram of the transmission and receiving system of the present invention including a transmission system **100** distributing to a plurality of users via a reception system **200** configured as a cable television system.

FIG. 1*e* shows a high level block diagram of the transmission and receiving system of the present invention including a transmission system **100** distributing to a plurality reception systems **200** and **200'**. In the configuration shown in FIG. 1*e*, reception system **200** is a direct connection system wherein a user is directly connected to transmission system **100**. Reception system **200'** preferably includes a first cable television system **200***a* and a second cable television system **200***b*. Users of cable television systems **200***a* and **200***b* are indirectly connected to transmission system **100**

FIG. 1*f* shows a high level block diagram of the transmission and receiving system of the present invention including transmission system **100** distributing via several channels to reception systems **200** and **200'**. Reception system **200** is preferably non-buffering. In such a system, users are directly connected to transmission system **100**, as in reception system **200** in FIG. 1*e*.

Reception system **200'** shown in FIG. 1*f* is a cable television system, as shown in reception system **200'** of FIG. 1*e*. In FIG. 1*f*, the reception system **200'** is preferably buffering, which means that users may receive requested material at a delayed time. The material is buffered in intermediate storage device **200***c* in reception system **200'**.

In the configuration of FIG. 1*f*, decompression of the requested material may preferably occur at the head end of a cable television reception system **200'**. Thus, distribution may be provided to users via standard television encoding methods downstream of the head end of the cable distribution system. This method is preferred for users who only have cable television decoders and standard television receivers.

FIG. 1*g* shows a high level block diagram of the transmission and receiving system of the present invention including transmission system **100** distributing to a reception system **200**, which then preferably transmits requested material over airwave communication channels **200***d*, to a plurality of users. The transmission and receiving system shown in FIG. 1*g* may preferably transmit either compressed or uncompressed data, depending on the requirements and existing equipment of the user. The airwave transmission and receiving system shown in FIG. 1*g* may preferably employ either VHF, UHF or satellite broadcasting systems.

With respect to the transmission and receiving systems set forth in FIGS. 1*a*–1*g*, the requested material may be fully compressed and encoded, partly decompressed at some stage in transmission system **100**, or fully decompressed prior to transmission. The reception systems **200** may either buffer the requested material for later viewing, or decompress in real time the requested material as it is distributed by transmission system **100**. Alternatively, the reception systems 200 of the present invention may perform a combination of buffering and non-buffering by buffering some of the requested material and decompressing the remainder of the requested material for immediate viewing as it is distributed by transmission system 100.

In direct connection configurations, such as reception systems 200 shown in FIGS. 1*e* and 1*f*, the user preferably selects the reception system 200 to which the requested material is sent, and optionally selects the time playback of the requested material as desired. Accordingly, the user may remotely access the transmission system 100 from a location different than the location of reception system 200 where the material will be sent and/or played back. Thus, for example, a user may preferably call transmission system 100 from work and have a movie sent to their house to be played back after dinner or at any later time of their choosing.

In non-direct connection reception systems such as shown in reception system 200' of FIG. if, intermediate storage device 200*c* may preferably include, for example, sixteen hours of random access internal audio and video storage. A reception system with such storage is capable of storing several requested items for future playback. The user could then view and/or record a copy of the decompressed requested material in real time, or compressed in non-real time, at a time of their choosing. Accordingly, the user would not have to make a trip to the store to purchase or rent the requested material.

In any of the transmission and receiving systems illustrate in FIGS. 1*a*–1*g*, the requested material may be copy protected. To achieve copy protection, the requested material, as an item, is encoded as copy protected during storage encoding in transmission system 100. The user may then play back the item only one time. The user may also optionally review select portions of the item prior to its automatic erasure from the memory of the reception system 200. In this way, requested material may be distributed to "view only" users and also to "view and copy" users who wish to retain copies of the distributed items.

Copy protected programs, when decompressed and played back would have a copy protection technique applied to the analog and digital output signals. The analog video output is protected from copying through the use of irregular sync signals, which makes the signal viewable on a standard television but not recordable on a audio/video recorder. The receiving system recognizes copy protected programs and disables the audio-video recorder. Digital output protection is effected through copy protect bit settings in the digital output signal, thus preventing a compatible digital recorder from recording the digital audio and/or video signal stream. A protected item will not be passed to the compressed data port of the digital recorder for off line storage.

FIGS. 2*a* and 2*b* illustrate detailed block diagrams of preferred implementations of the transmission system 100 of the present invention. Transmission system 100 may either be located in one facility or may be spread over a plurality of facilities. A preferred embodiment of transmission system 100 may preferably include only some of the elements shown in FIGS. 2*a* and 2*b*.

Transmission system 100 of a preferred embodiment of the present invention preferably includes source material library means for temporary storage of items prior to conversion and storage in a compressed data library means. The items of information may include analog and digital audio and video information as well as physical objects such as books and records which require conversion to a compatible media type before converting, compressing and storing their audio and video data in the compressed data library means.

As shown in FIG. 2*a*, the source material library means included in transmission system 100 preferably includes a source material library 111. The source material library 111 may include different types of materials including television programs, movies, audio recordings, still pictures, files, books, computer tapes, computer disks, documents of various sorts, musical instruments, and other physical objects. These materials are converted to or recorded on a media format compatible to the digital and analog inputs of the system prior to being compressed and stored in a compressed data library 118. The different media formats preferably include digital or analog audio and video tapes, laser disks, film images, optical disks, magnetic disks, computer tapes, disks and, cartridges.

The source material library 111, according to a preferred embodiment of the present invention, may preferably include a single source material library or a plurality of source material libraries. If there are a plurality of source material libraries, they may be geographically located close together or may be located far apart. The plurality of source material libraries may communicate using methods and channels similar to the methods and channel types which libraries may employ for communication with the receiving system 200 of the user, or the source material libraries may communicate via any available method.

Prior to being made accessible to a user of the transmission and receiving system of the present invention, the item must be stored in at least one compressed data library 118, and given a unique identification code by identification encoder 112. Storage encoding, performed by identification encoder 112, aside form giving the item a unique identification code, optionally involves logging details about the item, called program notes, and assigning the item a popularity code. Storage encoding may be performed just prior to conversion of the item for transmission to reception system 200, at any time after starting the conversion process, or after storing the item in the compressed data library 118.

In a preferred embodiment of the present invention, the method of encoding the information involves assigning a unique identification code and a file address to the item, assigning a popularity code, and inputting the program notes. This process is identical for any of the different media types stored in the source material library 111.

The transmission system 100 of the present invention also preferably includes conversion means 113 for placing the items from source material library 111 into a predetermined format as formatted data. In the preferred embodiment, after identification encoding is performed by identification encoder 112, the retrieved information is placed into a predetermined format as formatted data by the converter 113. The items stored in source material library 111 and encoded by identification encoder 112 may be in either analog or digital form. Converter 113 therefore includes analog input receiver 127 and digital input receiver 124. If items have only one format, only one type of input receiver 124 or 127 is necessary.

When the information from identification encoder 112 is digital, the digital signal is input to the digital input receiver 124 where it is converted to a proper voltage. A formatter 125 sets the correct bit rates and encodes into least significant bit (lsb) first pulse code modulated (pcm) data. Formatter 125 includes digital audio formatter 125*a* and digital video formatter 125*b*. The digital audio information is input into a digital audio formatter 125*a* and the digital video information, if any, is input into digital video formatter 125*b*. Formatter 125 outputs the data in a predetermined format.

When the retrieved information from identification encoder **112** is analog, the information is input to an analog-to-digital converter **123** to convert the analog data of the retrieved information into a series of digital data bytes. Converter **123** preferably forms the digital data bytes into the same format as the output of formatter **125**.

Converter **123** preferably includes an analog audio converter **123***a* and an analog video converter **123***b*. The analog audio converter **123***a* preferably converts the retrieved audio signal into pcm data samples at a fixed sampling rate. The analog video converter **123***b* preferably converts the analog video information, retrieved from identification encoder **123**, into pcm data also at fixed sampling rates.

If the retrieved information being converted contains only audio information, then the audio signal is fed to the appropriate digital audio input or analog audio input. When the retrieved information contains both audio and video information, the audio and video signals are passed simultaneously to the audio and video converter inputs. Synchronization between the audio and video data can be maintained in this way.

If, for example, the retrieved information to be converted from the source material library **111** is a motion picture film, the picture frames in the film are passed through a digital telecine device to the digital input receiver **124**. Format conversion is then preferably performed by digital video formatter **125***b*. Accompanying audio information is passed through an optical or magnetic digital playback device. This device is connected to digital audio formatter **125***a*.

In some cases, such as inter-library transfers, incoming materials may be in a previously compressed form so that there is no need to perform compression by precompression processor **115** and compressors **128** and **129**. In such a case, retrieved items are passed directly from identification encoder **112** to the compressed data formatter **117**. The item database records, such as the program notes which may also be input from another system, to the compressed data formatting section **117**, where this data, if necessary, is reformatted to make it compatible with the material stored in compressed data library **118**. Such material may be received in the form of digital tapes or via existing communication channels and may preferably input directly to a short term storage **117'** in the compressed data formatting section **117**.

The transmission system **100** of the present invention also preferably includes ordering means for placing the formatted information into a sequence of addressable data blocks. As shown in FIG. **2***a*, the ordering means in the preferred embodiment includes time encoder **114**. After the retrieved information is converted and formatted by the converter **113**, the information may be time encoded by the time encoder **114**. Time encoder **114** places the blocks of converted formatted information from converter **113** into a group of addressable blocks. The preferred addressing scheme employs time encoding. Time encoding allows realignment of the audio and video information in the compressed data formatting section **117** after separate audio and video compression processing by precompression processor **115** and compressor **116**.

The converted formatted information of the requested material is then preferably in the form of a series of digital data bytes which represent frames of video data and samples of the audio data. A preferred relationship of the audio and video bytes to each other is shown in FIG. **8**. Incoming signals are input and converted in sequence, starting with the first and ending with the last frame of the video data, and starting with the first and ending with the last sample of the audio data. Time encoding by time encoder **114** is achieved by assigning relative time markers to the audio and video data as it passes from the converter **113** through the time encoder **114** to the precompression processor **115**. Realignment of audio and video data, system addressing of particular data bytes, and user addressing of particular portions of items are all made possible through time encoding.

Through the use of the address of an item and its frame number it is possible to address any particular block of audio or video data desired. From here, further addressing down to the individual byte is possible. Frames and groups of frames may preferably be further broken down, as necessary to the individual bytes and bits, as required for certain processing within the system.

User and system addressing requirements dictate the level of granularity available to any particular section of the system. Users are able to move through data in various modes, thus moving through frame addresses at various rates. For example, a user may desire to listen to a particular song. They may preferably enter the song number either when requesting the item from the compressed data library **118** and only have that song sent to their receiving system **200** or they may preferably select that particular song from the items buffered in their receiving system **200**. Internal to the system, the song is associated with a starting frame number, which was indexed by the system operator via the storage encoding process. The system item database may contain information records for individual frames or groups of frames. These can represent still frames, chapters, songs, book pages, etc. The frames are a subset of, and are contained within, the items stored in the compressed data library **118**. Time encoding by time encoder **114** makes items and subsets of items retrievable and addressable throughout the transmission system **100**. Time encoding enables subsequent compression of the information to be improved because data reduction processes may be performed in the time dimension. This is described in greater detail below.

The transmission system **100** of the present invention also preferably includes data compression means for compressing the formatted and sequenced data. The sequence of addressable data blocks which was time encoded and output by time encoder **114** is preferably sent to precompression processor **115**. The data arriving from time encoder **114** may be at various frame rates and of various formats. Precompression processor **115** preferably includes audio precompressor **115***a* and video precompressor **115***b*.

Video precompression processor **115***b* buffers incoming video data and converts the aspect ratio and frame rate of the data, as required by compression processor **116**. The frame buffer **131** of video precompression processor **115***b* holds all incoming data until the data is compressed by the data compressor **116**. The incoming video data is processed for sample rate optimization, aspect ratio fitting and buffered in buffer **130** for compression processing by the video precompression processor **115***b*.

Video precompression processor **115***b* processes the incoming video data so that it fits into the aspect ratio of the transmission and receiving system of the present invention. When incoming material with a different aspect ratio than the aspect ratio of-the system is selected, a chosen background is preferably placed around the inactive region of the video information. In this way, no data is lost to differences in the aspect ratio between incoming material, and the converted and compressed data stored in the transmission system **100**. Images resulting from a different aspect ratio may have an inactive region where background information is contained, or may be converted into a best fit arrangement. Output from the video precompression processor 115*b* is stored in the frame buffer 131, which is dual ported and is directly addressable by video compressor 129.

The incoming audio data is processed for sample rate and word length optimization and is then buffered in buffer 130 for compression processing by the audio precompression processor 115*a*. Audio precompression processor 115*a* may preferably transcode incoming audio information, as required, to create the optimum sample rate and word lengths for compression processing. The output of the audio precompression processor 115*a* is a constant sample rate signal of a fixed word length which is buffered in frame buffer 130. The frame buffer 130 is dual ported and is directly addressable by audio compressor 128. Blocking the audio data into frames at audio precompression processor 115*a* makes it possible to work with the audio data as addressable packets of information.

Once precompression processing is finished, the frames are compressed by the data compressor 116. Compressor 116 preferably comprises an audio data compressor 128 and a video data compressor 129. The benefits of data compression performed by data compressor 116 are shortened transmission time, faster access time, greater storage capacity, and smaller storage space requirements. Compression processing performed by compressors 128 and 129 requires multiple samples of data to perform optimum compression. Audio and video information is preferably converted into blocks of data organized in groups for compression processing by audio compressor 128 and video compressor 129, respectively. These blocks are organized as frames, and a number of frames are contained respectively in the buffers 130 and 131. By analyzing a series of frames it is possible to optimize the compression process.

Audio data is preferably compressed by audio compressor 128 by application of an adaptive differential pulse code modulation (ADPCM) process to the audio data. This compression process, which may be implemented by the apt-x 100 digital audio compression system, is manufactured by Audio Processing Technology (APT). Audio compression ratios of 8× or greater are achieved with the APT system.

Compression by compressor 116 may be performed on a group of 24 video frames may preferably be passed in sequence to the frame buffer 130 of the video precompression processor 115*b* where they are analyzed by video compressor 129 which performs data reduction processing on the video data. Video compression is preferably performed by video compressor 129. Video compression is achieved by the use of processors running algorithms designed to provide the greatest amount of data compression possible. Video data compression preferably involves applying two processes: a discrete cosine transform, and motion compensation. This process is described in "A Chip Set Core of Image Compression", by Artieri and Colavin. Multiple frames of video data may preferably be analyzed for patterns in the horizontal (H), vertical (V), diagonal (zigzag) and time.(Z) axis. By finding repetition in the video data, redundancy may be removed and the video data may be compressed with a minimal loss of information.

In accordance with a preferred embodiment of the present invention, the transmission system 100 may further comprise compressed data storing means, coupled to the compression means, for storing as a file the compressed sequenced data with the unique identification code received from the data compression means. After compression processing by compressor 116, the compressed audio and video data is preferably formatted and placed into a single file by the compressed data storage means 117. The file may contain the compressed audio and/or video data, time markers, and the program notes. The file is addressable through the unique identification code assigned to the data by the identification encoder 112.

Further, according to the present invention, the transmission system preferably includes compressed data library means for separately storing composite formatted data blocks for each of the files. The compressed data storage means preferably includes compressed data library 118, as shown in FIG. 2*b*. After the data is processed into a file by the compressed data storage means 117, it is preferably stored in a compressed data library 118. In a preferred embodiment, compressed data library 118 is a network of mass storage devices connected together via a high speed network. Access to any of the files stored in compressed data library 118 is available from multiple reception systems 200 connected to the transmission and receiving system.

Stored items are preferably accessed in compressed data library 118 through a unique address code. The unique address code is a file address for uniquely identifying the compressed data items stored in the compressed data library section of a library system. This file address, combined with the frame number, and the library system address allow for complete addressability of all items stored in one or more compressed data libraries 118. Compressed data library addresses along with receiving system addresses are used to form a completely unique address for distribution system control.

The unique address code is an address assigned to the item by the system operator during storage encoding, which is preferably done prior to long term storage in the compressed data library 118. In a preferred embodiment, the unique address code is used for requesting and accessing information and items throughout the transmission and receiving system. The unique address code makes access to the requested data possible.

The storage encoding process performed by encoder 112 also allows entry of item notes and production credits. Production credits may include the title, names of the creators of the item such as the producer, director, actors, etc. Other details regarding the item which may be of interest and which may make the items more accessible are kept in an item database.

Item addresses are mapped to item names by identification encoder 112 and may preferably be used as an alternative method of accessing items. The item names are easier to remember, thus making user access more intuitive by using item names. The storage encoding entry process performed in identification encoder 112 operates a program which updates a master item database containing facts regarding items in the compressed data library system. The storage encoding process may be run by the system operator whereby the system operator accesses the master item database to track and describe items stored in one or more compressed data libraries. The names and other facts in the item database may preferably be updated at any time via the storage encoding process. Changes made to the master item database may be periodically sent to the remote order processing and item database 300.

As described in more detail later, a user may preferably access an item via its unique identification code, via its title or the user may use other known facts for accessing an item. The user may access items in the compressed data library 118 direct using the unique address code or the user may

Exhibit 11 Page 139

obtain access via the remote order processing and item database **300**. Indirect access via the remote order processing and item database **300** is possible using, for example, a synthesized voice system, a query type of computer program interface, or customer assistance operators. In addition to providing interactive access to the remote order processing and item database **300**, a catalog listing some or all available titles may also preferably be published. With a published catalog, users may obtain the unique address code for an item very easily thereby allowing for retrieval from the compressed data library **118** without any help from an interactive system.

To achieve user access via an interactive system, facts about the items may be kept in files as a part of the items or the facts may be kept separately, for example, by systems which only to inform users of the available items and take orders. For example, in systems which have portions split in separate locations, the facts about the items may be separated from the items themselves and stored in separate files. A system of this type can distribute user orders to other portions of the transmission and receiving system for ultimate distribution to the requesting user. Further, to support a plurality of users, multiple versions of the item database may preferably reside either on multiple database servers, in catalogs, or on other computer systems.

The item database master may reside in the system control computer **1123** where may be updated and kept current to the contents of the compressed data library **118**. The data stored in the item database master may be accessed by users via application programs, running on the system control computer **1123**, and on the reception system **200** of the user. Users may connect to the item database via any available telecommunication channels. Copies of the item database master may be updated and informed of new entries into compressed data library **118** at periodic intervals determined by the system manager.

Other copies of the item database master may also be made available to users from the remote order processing and item database **300** which batch processes and downloads user requests to the control computer **1123** of the compressed data library **118** via standard telecommunications or high speed communication channel. Moreover, multiple remote order processing and item database **300** sites make it possible for more locations to process orders than there are library facilities, and thus make order processing more efficient.

Preferably, access of a requested item via the remote order processing and item database **300** operates as follows. If the user does not know the title of the desired item, he or she may request the item by naming other unique facts related to the item. For example, a user would be able to access an item about Tibetan Medicine by asking for all items which include information about "Tibet" and include information about "Medicine." The remote order processing and item database **300** would then be searched for all records matching this request. If there is more than one item with a match, each of the names of the matching items are preferably indicated to the user. The user then selects the item or items that he or she desires. Upon selection and confirmation, by the user, a request for transmission of a particular item or items is sent to the distribution manager program of the system control computer **1123**. The request contains the address of the user, the address of the item, and optionally includes specific frame numbers, and a desired viewing time of the item.

The storage encoding process performed by identification encoder **112** also allows entry of a popularity code. The popularity code is preferably assigned on the basis of how often the corresponding item is expected to be requested from the compressed data library **118**. This popularity code can be used to determine the most appropriate form of media for storage of the compressed data in a mixed media system. Mixed media systems are preferably employed as more cost effective storage in very large compressed data libraries **118**. Once assigned, the popularity code may be dynamically updated, by factoring item usage against system usage. Thus, stored items are dynamically moved to the most appropriate media over their life in the compressed data library **118**. If a particular item stored in compressed data library **118** is retrieved frequently by users, storage in compressed data library **118** is preferably on higher speed, more reliable, and probably more expensive media. Such media includes Winchester and magneto-optical disks.

If an item stored in compressed data library **118** is retrieved less frequently, it may be stored in the compressed data library **118** on a digital cassette tape. Examples of such cassette tapes are a Honeywell RSS-600 (Honeywell Inc. Minneapolis Minn.), Summus JukeBoxFilm and tape library (Summus Computer Systems, Houston, Tex. 800-255-9638), or equivalent cassette tapes. All items stored in the compressed data library **118** are on line and are connected to the high speed network. Thus, they may be readily accessed.

Instead of using a remote order processing and item database **300**, the compressed data library **118** may include the program notes which were input by the system operator. The program notes may preferably include the title of the item stored in the compressed data library **118**, chapter or song titles, running times, credits, the producer of the item, acting and production credits, etc. The program notes of an item stored in the compressed data library **118** may be thus contained within the compressed data file formed in the compressed data formatter **117**.

In some cases, where multiple compressed data libraries **118** are organized, the popularity code may dictate distribution of a particular item to multiple distribution systems. In such cases, a copy of the compressed data is sent to another library and the other library can then distribute the compressed data to users concurrently with the original compressed data library **118**.

The compressed data library **118** is composed of a network of storage devices connected through a High Performance Parallel Interface (HPPI) Super Controller (available from Maximum Strategy Inc., San Jose, Calif.). Therefore, multiple communication controllers may preferably access the large quantity of data stored in compressed data library **118** at very high speeds for transfer to a reception system **200** of a user upon request. For more details on this configuration see Ohrenstein, "Supercomputers Seek High Throughput and Expandable Storage", Computer Technology Review, pp. 33–39 April 1990.

The use of an HPPI controller allows file placement onto multiple mass storage devices of the compressed data library **118** with a minimum of overhead. Database management software controls the location and tracking of the compressed data library **118** which can be located across multiple clusters of file servers connected together by one or more high speed networks over multiple systems.

The transmission system **100** of the present invention may also preferably include library access/interface means for receiving transmission requests to transmit items and for retrieving formatted data blocks stored in the compressed data library **118** corresponding to the requests from users. The compressed audio and/or video data blocks, along with any of the information about the item stored in the compressed data library **118** may be accessed via library access interface **121**. The library access interface **121** receives transmission requests either directly from the users or indirectly by remote order processing and item database **300**.

The transmission format means **119** receives the request and retrieves the composite formatted data block of the requested item stored in compressed data library **118** and converts the compressed formatted data block into a format suitable for transmission. The requested item is then sent to the user via the transmitter **122** or directly via interface **121**.

In a preferred embodiment of the present invention, customer access of an item stored in compressed data library **118** via the library access interface **121** may be performed in various ways. The methods of requesting a stored item are analogous to making an airline reservation or transferring funds between bank accounts Just as there are different methods available for these processes it is desirable to have several ordering methods available to the users of the system of the present invention. For example, telephone tone decoders and voice response hardware may be employed. Additionally, operator assisted service or user terminal interfaces may be used.

Customer access via telephone tone decoders and voice response hardware is completely electronic and may preferably be performed between a system user and a computer order entry system. The user may obtain help in ordering an item from a computer synthesized voice. With such an access method, the user will normally be accessing a dynamic catalog to assist them. Confirmation of selections and pricing information may preferably be given to the user prior to completion of the transaction.

This process of access, performed by remote order processing and item database configuration **300**, shown in FIG. 1*c*, preferably includes the following steps, shown in flowchart **3000** of FIG. **3**. First, the user calls the system access number (step **3010**). Upon successfully dialing the system access number, the user receives instructions from the system (step **3020**). The instructions may preferably include steps the user must take in order to place an order. Preferably, the instructions may be bypassed by the experienced user who knows how to place an order.

The user then enters a customer ID code by which the system accesses the user's account, and indicates to the system that the user is a subscriber of the system (step **3030**). In response to the user entering his ID code in step **3030** the system confirms whether the user is in good standing (step **3040**). If the user is in good standing, the system queues the user to input his request (step **3050**).

The user request may preferably be made from a catalog sent to each of the subscribers of the system. The user will preferably identify his choice and enter the corresponding identification code of the item (step **3060**). The system then preferably confirms the selection that the user has made and informs the user of the price of the selection (step **3070**).

The user then indicates whether the confirmation performed in step **3070** is correct (step **3080**). If the confirmation performed in step **3070** is correct, the user so indicates and then inputs a desired delivery time and delivery location (step **3090**).

If the confirmation performed in step **3070** does not result in the selection desired by the user, the user re-inputs the item identification code in step **3060** and the confirmation steps **3070** and **3080** are repeated. Therefore, proper selection of the selected item is insured. Once there is confirmation, the user enters the playback time and destination in step **3090**.

The user then preferably confirms that the order is correct (step **3100**). The confirmation performed in step **3100** includes confirmation of the entire transaction including the selected item, the selected time of playback, and the location of playback The transaction is then completed and the request is placed on a transmission queue at the appropriate compressed data library **118** (step **3110**).

Access by the users via operator assisted service includes telephone operators who answer calls from the users. The operators can sign up new customers, take orders, and help with any billing problems. The operators will preferably have computer terminals which give them access to account information and available program information. Operators can also assist a user who does not know a title by looking up information stored in files which may contain the program notes, as described above. Once the chosen program is identified, the operator informs the user of the price. After the user confirms the order, the user indicates the desired delivery time and destination. The operator then enters the user request into the system. The request is placed in the transmission queue.

Access by a user terminal interface method provides the user with access from various terminals including personal computers, and specialized interfaces built into the reception system **200** for the user. Such access allows a user to do a search of available programs from a computer screen. This process involves the steps **4000** shown in FIG. **4**.

FIG. **4** is a flowchart of a preferred method of user request via a user interface of the present invention. In the preferred method of FIG. **4**, the user first logs onto the user terminal interface (step **4010**). After the user logs on, the user may preferably select a desired item by searching the database of available titles in the library system control computer **1123** or any remote order processing and item database **300** (step **4020**). The search may preferably be performed using the database containing the program notes, described above with respect to FIGS. 2*a* and 2*b*. It is possible to process orders and operate a database of available titles at multiple locations remote of the source material library **111**. Users and order processing operators may preferably access such remote systems and may place transmission requests from these systems. Orders placed on these systems will be processed and distributed to the appropriate libraries. After the desired item is found, the user selects the item for transmission at a specific time and location (step **4030**).

To complete an order, the remote order processing and item database **300** preferably connects to the compressed data library **118** of choice via the library access interface **121** and communicates with the library system control computer **1123**. Preferably the user's account ID, identification of the item for transmission and the chosen destination for the item are communicated. Through employment of distributed order processing systems of this type many orders may be processed with minimal library overhead.

All transmission requests from the access methods are placed into a transmission queue managed by the library system control computer **1123**. This queue is managed by a program that controls the distribution of the requested items to the reception system **200** of the user. The queue manager program also operates in the system control computer and keeps track of the user ID, the chosen program and price, the user channel type, the number of requests for a given program, the latest delivery time, and the compressed data library media type (for example, high speed or low speed). From this information, the queue manager program makes best use of the available distribution channels and media for efficient transmission and storage of the requested items.

The queue manager program also manages the file transmission process for multiple requests for a single file, stored in the compressed data library **118**. During a given time period, the queue manager program will optimize access to the compressed data library **118**, wherever possible it will place the data on multiple outputs for simultaneous transmission to more than one requesting user.

The conversion performed by transmission data converter **119** encodes the data for the transmission channel. The transmission data converter transfers the desired segments of data from the compressed data library **118** onto the communication channel which is used to deliver the data to the reception system **200**.

The transmission system **100** of the present invention preferably further includes transmitter means **122**, coupled to the compressed data library **118**, for sending at least a portion of a specific file to at least one remote location. The transmission and receiving system of the present invention preferably operates with any available communication channels. Each channel type is accessed through the use of a communications adaptor board or processor connecting the data processed in the transmission format converter **119** to the transmission channel.

A preferred embodiment of the present invention also includes means by which to access users via common access lines. These may include standard telephone, ISDN or B-ISDN, microwave, DBS, cable television systems, MAN, high speed modems, or communication couplers. Metropolitan Area Networks (MANS) which are common carrier or private communication channels are designed to link sites in a region. MANs are described by Morreale and Campbell in "Metropolitan-area networks" (IEEE Spectrum, May 1990 pp. 40–42). The communication lines are used to transmit the compressed data at rates up to, typically, 10 Mb/sec.

In order to serve a multitude of channel types, a preferred embodiment of the present invention includes a multitude of output ports of each type connected to one or more computers on the transmission and receiving system. The management of transmission is then distributed. That is, the computer controlling the transmission queue tells the transmission encoding computer its task and then the task is executed by the transmission encoding computer, independent of the transmission queue computer. The transmission queue computer provides the data for transmission by file server which also distributes to other transmitters located in the same or other transmission encoding computers.

FIG. **5** is a flowchart of a preferred method of implementing a queue manager program of the present invention. The queue manager program, in the distribution process, preferably confirms availability of an item from the compressed data library **118** and logically connects the item stored in compressed data library **118** to the communications controller, illustrated in FIG. 2*a* (step **5010**). After availability is confirmed in step **5010**, the data awaits transmission by the transmitter **122**.

After availability is confirmed in step **5010**, the communications controller preferably makes the physical connection to the reception system **200** of the user (step **5020**). This is normally done by dialing the receiving device of the user. The reception system **200** preferably answers the incoming call and confirms the connection (step **5030**).

Once connected to the reception system **200**, in steps **5020** **5030**, the data stored in compressed data library **118** is preferably transferred in data blocks from the compressed data library **118** to the communications controller (step **5040**). The data blocks are buffered by the communications controller. The buffered data is sent down the communications channel to the reception system **200** by transmitter **122** (step **5050**).

The transmitter **122** places the formatted data onto the communications channel. This is an electrical conversion section and the output depends upon the chosen communication path. The signal is sent to the reception system **200** in either a two way or a one way communication process. In a standard telephone connection, the transmitter **122** is preferably a modem. When using an ISDN channel, the transmitter **122** is preferably a data coupler.

In a preferred embodiment of the present invention, many forms of communication channels may be employed. Distribution of information is by common carrier communication channels whenever possible. These channels include common telephone service, ISDN and Broadband ISDN, DBS, cable television systems, microwave, and MAN.

In order that reception is performed efficiently, the reception system **200** confirms reception of the initial data block before receiving the remaining data blocks whenever possible (step **5060**). After all data blocks have been received and reception is confirmed, the communications controller breaks the physical connection to the reception system **200** (step **5070**). Then, confirmation of the transmission is sent to the queue manager (step **5080**). Finally, the queue manager updates the list and sends the information to the billing program, which updates the account of the user (step **5090**).

When item distribution occurs through a broadcasting method such as a communications satellite, the process is one way, with ongoing reception not being confirmed by the reception system **200**. In these situations, some further redundancy is included by transmission formatter **122** with the data blocks for error correction processing to be performed in the reception system **200**. In such one way communication situations, the queue manager program running in library system control computer **1123** confirm reception, via telephone line connection for example, to the reception system **200** after distribution. This should occur prior to updating the user's account and the dispatch lists.

The real time output signals are output to a playback system such as an audio amplifier and/or television. This output may also be sent to an audio/video recorder for more permanent storage. Moreover, in the preferred embodiment only non-copy protected data can be recorded on an audio/video recorder. Any material which is copy protected will be scrambled at the video output in a way which makes it viewable on a standard audio/video receiver but does not allow for recording of the material.

The reception system **200** has playback controls similar to the controls available on a standard audio/video recorder. These include: play, fast forward, rewind, stop, pause, and play slow. Since items are preferably stored on random access media, the fast forward and rewinding functions are simulations of the actual events which occur on a standard audio/video recorder. Frames do not tear as on an audio/video recorder, but in fast play modes they go by very quickly.

The library access interface **121** in the reception system **200** preferably includes a title window where a list of available titles are alphabetically listed. This window has two modes: local listing of material contained within the library system control computer **1123**, and library listing for all available titles which may be received from the available, remotely accessible libraries. The titles listed in this window are sent from the database on the library system control computer **1123** or the remote order processing and item database **300**.

The system may also preferably include dispatching control software which receives input from the remote order processing and item database **300** and sends distribution requests to the distribution systems. In instances where not all items are contained in each of the compressed data libraries **118**, the dispatching software will keep a list of the available titles in a particular compressed data library **118**. The dispatch software may also preferably coordinate network traffic, source material library **111** utilization, source material library **111** contents, and connection costs. By proper factoring of these variables, efficient use of the available distribution channels may be achieved.

FIG. **6** illustrates a block diagram of a preferred implementation of the reception system **200** according to the present invention. The reception system **200** is responsive to user requests for information stored in source material library **111**. The reception system **200** includes transceiver **201** which receives the audio and/or video information transmitted by transmitter **122** of the transmission system **100**. The transceiver **201** automatically receives the information from the transmitter **122** as compressed formatted data blocks.

The transceiver **201** is preferably connected to receiver format converter **202**. The receiver format converter **202** converts the compressed formatted data blocks into a format suitable for playback by the user in real time.

In the reception system **200** of the present invention, the user may want to play back the requested item from the source material library **111** at a time later than when initially requested. If that is the case, the compressed formatted data blocks from receiver format converter **202** are stored in storage **203**. Storage **203** allows for temporary storage of the requested item until playback is requested.

When playback is requested, the compressed formatted data blocks are sent to data formatter **204**. Data formatter **204** processes the compressed formatted data blocks and distinguishes audio information from video information.

The separated audio and video information are respectively decompressed by audio decompressor **209** and video decompressor **208**. The decompressed video data is then sent simultaneously to converter **206** including digital video output converter **211** and analog video output converter **213**. The decompressed audio data is sent simultaneously to digital audio output converter **212** and analog audio output converter **214**. The outputs from converters **211–214** are produced in real time.

The real time output signals are output to a playback system such as a TV or audio amplifier. They may also be sent to an audio/video recorder of the user. By using the reception system **200** of the present invention, the user may utilize the stop, pause, and multiple viewing functions of the receiving device. Moreover, in a preferred embodiment of the present invention, the output format converters may be connected to a recorder which enables the user to record the requested item for future multiple playbacks.

FIG. **7** is a flow chart **400** of a preferred method of distribution of the present invention. The distribution method is preferably responsive to requests identifying information to be sent from the transmission system **100** to remote locations. Method **400** assumes that the items have already been stored in compressed data library **118**.

As illustrated in FIG. **7**, the first step of the distribution method **400** involves retrieving the information for selected items in the source material library ill, upon a request by a user of the distribution system (step **412**). This is analogous to taking books off of a shelf at the local public library after the person has decided that he or she would like to read them.

After the information for the selected items is retrieved in step **412**, the distribution method **400** of the present invention further comprises the step of processing the information for efficient transfer (step **413**). The processing performed in step **413** preferably includes assigning a unique identification code to the retrieved information performed by identification encoder **112**, shown and described with respect to FIG. 2*a* (step **413***a*). The processing also preferably includes placing the retrieved information into a predetermined format as formatted data by converter **113** (step **413***b*), and placing the formatted data into a sequence of addressable data blocks by ordering means **114** (step **413***c*).

Processing step **413** also includes compressing the formatted and sequenced data performed by data compressor **116** (step **413***d*), and storing as a file the compressed sequenced data received from the data compression means with the unique identification assigned by the identification encoding means (step **413***e*).

After the information is processed for efficient transfer, in substeps **413***a–e* of step **413**, the distribution method **400** of the present invention preferably includes the step of storing the processed information is stored in a compressed data library (step **414**). Preferably, the compressed data library is analogous to compressed data library **118**, described with respect to FIG. 2*a*.

After the information is stored in a compressed data library **118**, the transmission and receiving system preferably waits to receive a transmission request (step **415**). Upon receiving a transmission request, from transmission system **100**, the compressed formatted data is preferably converted for output to a reception system **200**, selected by the user. The information is preferably transmitted over an existing communication channel to a reception system **200**, and is received by that system (step **417**). When the information is received in step **417**, it is preferably formatted the particular type of reception system **200** to which the information is sent.

The received information is preferably buffered (step **418**) by a storage means analogous to element **203** shown in FIG. **3**. The information is preferably buffered so that it may be stored by the user for possible future viewings. The requested information is then played back to the reception system **200** of the user at the time requested by the user (step **419**).

FIGS. **8***a*–**8***e* are block diagrams of preferred implementations of data structures and data blocking for items in the audio and video distribution system. FIG. **8***a* shows the block structure of video data where a video frame **812** is composed of a plurality of video samples **811**, and a second of video **813** is composed of a plurality of video frames **812**.

FIG. **8***b* shows the block structure of audio data where an audio data frame **822** is composed of a plurality of audio samples **821**, and a second of audio **823** is composed of a plurality of audio data frames **822**. FIG. **8***c* shows the block structure of a data frame **832** composed of a plurality of data bytes **831**. The combination of the audio frames **812**, video frames **822**, and data frames **832** comprise the elements of a single item. FIG. **8***d* shows a block representation of for three illustrative items which may be stored in the source material library **111**. Each of items **1–3** contains its own arrangement of video frames **812**, audio frames **822**, and data frames **832**.

FIG. **8***e* shows methods of distribution to reception systems **200** with both multiplexed and non-multiplexed signal paths, both addressed and non-addressed blocks of items. A block of an item may be an entire item or, alternatively, may be only a portion of an item, as selected by a user. Further, the blocks may composed of either compressed, partially compressed, or fully decompressed data, as required by the configuration of the reception system **200**.

As shown in FIG. *8e*, the same block, for example, block 1, may be simultaneously transmitted over different distribution channels. The blocks when transmitted over one of the distribution channels may have receiver addresses appended to the blocks or the reception system **200** may have been preconfigured to receive the blocks comprising data frames for particular items from the active distribution channel.

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with the true scope and spirit of the invention being indicated by the following claims.

What is claimed is:

1. A transmission system responsive to input from a user positioned at an accessing location for transmitting information to a premises selected by the user, the transmission system comprising:
   - a plurality of libraries for storing items containing information;
   - identification encoding means for retrieving the information in the items from the plurality of libraries and for assigning a unique identification code to the retrieved information;
   - conversion means, coupled to the identification encoding means, for placing the retrieved information into a predetermined format as formatted data; and
   - transmitter means, coupled to the conversion means, for transmitting the formatted data to the premises selected by the user, wherein the premises selected by the user is not limited to a predetermined user premises.

2. A transmission system as recited in claim **1**, wherein the plurality of libraries are geographically separated.

3. A transmission system as recited in claim **1**, wherein the premises selected by the user is geographically separated from the accessing location.

4. A digital audio/video communication network comprising:
   - a reception system in data communication with a plurality of subscriber selectable receiving stations, the reception system comprising,
     - means for receiving compressed, digitized data representing at least one item of audio/video information at a non-real time rate,
     - means for storing a complete copy of the received compressed, digitized data, and
     - means, responsive to the stored compressed, digitized data, for transmitting a representation of the at least one item of audio/video information at a real-time rate to at least one of the plurality of subscriber selectable receiving stations, wherein said means for receiving, said means for storing, and said means for transmitting are positioned at the same location, and wherein the at least one of the plurality of subscriber selectable stations is located at a premises geographically separated from the location of the reception system.

5. A digital audio/video communication network as recited in claim **4**, wherein the means for transmitting comprises a converter for decompressing the compressed digitized data representing the at least one item of audio/video information.

6. A digital audio/video communication network as recited in claim **4**, further comprising a processing station for formatting items of audio/video information as compressed, digitized data and transmitting the compressed, digitized data representing at least one item of audio/video information at the non-real time rate to the means for receiving.

7. A digital audio/video communication network as recited in claim **6**, wherein the processing station comprises:
   - means for inputting items of audio/video information;
   - conversion means for placing each input item of audio/video information into a predetermined format as formatted data;
   - compression means for compressing the formatted data; and
   - transmitter means for sending compressed formatted data for the at least one item of audio/video information at the non-real time rate to the reception system.

8. A method of distributing audio/video information comprising:
   - transmitting compressed, digitized data representing a complete copy of at least one item of audio/video information at a non-real time rate from a central processing location to a local distribution system remote from the central processing location;
   - receiving, into a receiving means, the transmitted compressed, digitized data representing a complete copy of the at least one item;
   - storing, in a storing means, the received compressed, digitized data representing the complete copy of the at least one item at the local distribution system; and
   - in response to the stored compressed, digitized data, transmitting, using a transmitting means, a representation of the at least one item at a real-time rate to at least one of a plurality of subscriber selectable receiving stations coupled to the local distribution system, wherein the receiving means, the storing means, and the transmitting means are positioned at the same location, and wherein the at least one of the plurality of subscriber selectable stations is located at a premises geographically separated from the local distribution system.

9. A method as recited in claim **8**, further comprising the step of decompressing the compressed, digitized data representing the complete copy of the at least one item of audio/video information before the transmitting step.

10. A method as recited in claim **9**, wherein the decompressing step is performed in the local distribution system to produce the representation of the at least one item for transmission to the at least one of the plurality of subscriber selectable receiving stations.

11. A method of distributing audio/video information comprising:
   - formatting items of audio/video information as compressed digitized data at a central processing location;
   - transmitting compressed, digitized data representing a complete copy of at least one item of audio/video information from the central processing location;
   - receiving, into a receiving means, the transmitted compressed, digitized data representing a complete copy of the at least one item of audio/video information at a local distribution system;
   - storing, in a storing means, the received compressed, digitized data representing the complete copy of the at least one item at the local distribution system; and

using the stored compressed, digitized data to transmit using a transmitting means a representation of the at least one item to at least one of a plurality of subscriber selectable receiving stations coupled to the local distribution system, wherein the receiving means, the storing means, and the transmitting means are positioned at the same location, and wherein the at least one of the plurality of subscriber selectable stations is located at a premises geographically separated from the location of the local distribution system.

* * * * *